

REVISIONS				
ISS	ZONE	DESCRIPTION\PER REQUEST\DATE		

FLARE TO Ø8.3 ±0.07
(1/4" ±0.07)

FORMING (1.25)

25 REF.

RECOMMENDED
CABLE STRIPPING DIM'S
(«0A3-e½u?0?o

NOTES: FINISH (PLATING THICKNESS IN MICRO-INCHES)

- BRASS PER QQ-B-626
- BRASS PER QQ-B-613
- NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE
- NICKEL PL. 200 MIN. THICK OVER COPPER STRIKE
- GOLD PL. 3 MIN. THICK OVER NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE
- TEFLON MIL-P-19468
- JIS H 3250, C 2700

1. CRIMPED FERRULE
HEX CRIMP SIZE .178"
2. CRIMPED CONTACT PIN
SQ. CRIMP SIZE .043"

9	FERRULE	NOTE 7	NOTE 3	1	FR-51/445X127
8	CONTACT PIN	NOTE 1	NOTE 5	1	10-03001-204-8-076-B
7	WASHER	NOTE 2	NOTE 3	1	WS-128/9X08
6	SPRING	SK5	NOTE 4	1	B50000-6
5	RETAINER RING	NOTE 1	NOTE 3	1	B50000-5
4	GASKET	RUBBER	RED	1	GS-115/8X15
3	INSULATOR	NOTE 6	NATURAL	1	10-03001-204-3-A
2	BODY	NOTE 1	NOTE 3	1	B50000-2-38/27
1	SHELL	NOTE 1	NOTE 3	1	B50000-1-B

DIMENSIONS ARE IN MILLIMETERS				PART NO.		Amphenol - Kai Jack TAINAN TAIWAN
UNLESS OTHERWISE SPECIFIED TOLERANCES				APPROVED	DATE	
0.5-6 = ±0.2 6-30 = ±0.4 30-120 = ±0.6 120-315 = ±1 315-1000 = ±1.6 1000-2000 = ±2.4				CHECKED	DATE	
SCALE 3/1				DRAWN	DATE	
NO. DESCRIPTION MATERIAL FINISH Q'TY DRAWING NO.				05-10-00'		TITLE BNC CRIMP PLUG (FOR BELDEN 1865A CABLE)
1 2 3 4 5 6 7 8				05-10-00'		DRAWING NO. KJ-B1121A9-NT3G-1865A-75
1 2 3 4 5 6 7 8				05-10-00'		FILE NO. F:\DWG\B\1121A9\1865A-75\NT3G